

**Doseerwagen
MSR H308GII + WCR + EC meter
HW-nr.: 0330975**



Technische specificaties

- Doseerwagen met 4x 400x8-4ply wielen, trekboom en parkeerrem op achterwiel
- Weri Compact Roller gemonteerd op doseerwagen, 1" doorlaat, slanggeleider voor 3/4" slang, manuele variator voor traploos regelbare oprolsnelheid (0-55 mtr./min), Tele Radio handzender om de Weri Compact Roller op afstand aan/uit te zetten en af te remmen, maximale bereik: ±100 mtr. (afhankelijk van omstandigheden), elektrische vrijlooppkoppeling, instelbare aflooprem en elektromotor 400V 3 fase 50 Hz
- Doseerunit MSR, type H308GII
- Proportionele doseercapaciteit, tank A: 2-20 liter/M³
tank B: 2-20 liter/M³
- Gietcapaciteit: min./max. 500-8000 ltr./uur ⇔ 0,5 Bar min. 10 Bar max. drukverlies: ΔP 0,7 bar
- Onnauwkeurig meetbereik doseerpomp: < 2 %
- Temp. max.: 40°C
- Kranen om zowel water en/of mestoplossing met water te doseren
- CMR10 EC-meter regelaar met alarm, meetbereik: 0-1 of 0-10 EC
- MEC 12 EC-sensor
- 2x 50 ltr. PE tanken
- 30 ltr. mengvat
- SDF filter met uitwisselbaar element
- 10 mtr. snoer met rode CE-stekker
- Behuizing gehele installatie spatwaterdicht
- L x B x H: ±198x93x144 cm
- Gewicht: ±330 kg
- Opties: 50 mtr. Turboflex 3/4" slang
automatische afslag
easypress pomp (t.b.v. drukverhoging) + doorstroombeveiliging

**Dose wagon
MSR H308GII + WCR + EC indicator
HW-no.: 0330975**



Technical specifications

- Dose wagon with 4x 400x8-4ply wheels, towbar and parking brake on rear wheel
- Weri Compact Roller mounted on dose wagon, 1" swivel, hose guide for 3/4" hose, continuously variable roll up speed (0-55 mtr./min) manually controlled, radiographic control for on/off and brake by Tele Radio transmitter, max. reach: ±100 mtr. (depending on circumstances), electric freewheel clutch, adjustable roll off brake and electric motor 400V 3 phase 50 Hz
- Dosing feeder MSR, type H308GII
- Proportional dosing capacity, barrel A: 2-20 liter/M³
barrel B: 2-20 liter/M³
- Water capacity: min./max. 500-8000 ltr./hour ⇔ 0,5 Bar min. 10 Bar max. loss of pressure: ΔP 0,7 Bar
- Inaccurate measuring dosing feeder: <2 %
- Temp. max.: 40°C
- Dosing valve for water and/or fertiliser with water
- CMR10 EC-indicator with alarm, measuring: 0-1 or 0-10 EC
- MEC 12 EC-sensor
- 2x 50 ltr. PE tanks
- 30 ltr. mixing barrel
- SDF filter with exchangeable element
- 10 mtr. cord with red CE-plug
- Hosing installation splash water tight
- L x W x H: ±198x93x144 cm
- Weight: ±330 kg
- Option: 50 mtr. Turboflex 3/4" hose
automatic reduction
easypress pump (for pressure increase) + flow protection