

**KILVERBORD
RW280TK W.DU.E.M.PROP (dubbele ontvangers)
HW-nr.: 1108280**



Technische specificaties

- Accumulator pressostaat systeem
- Werkbreedte: 283 cm met gesloten deuren, 391 cm met open deuren (alleen bij afwerken)
- Een verstelbaar trekoog cat. 3 Ø37,6 mm
- Hoogte egaliseerbord: ±110 cm
- Opgebouwd met onafhankelijke wielophanging:
 - 1 hydraulische cilinder voor hoogteverstelling en vlakstelling links
 - 1 hydraulische cilinder voor hoogteverstelling en vlakstelling rechts
- 4 wielen BKT 19.0/45-R17/10PR AW-708, 49 cm breed met elk één afschraper
- 2 hydraulische deuren met onafhankelijke bediening vanaf secundaire controlbox
- Handmatig in hoogte verstelbare masten
- Secundaire controlbox voor bediening van hydraulische deuren en automatische of manuele hoogteregeling van het egaliseerbord
- Compleet met bekabeling en hydraulische aansluiting
- Voedingsspanning: 12 of 24 VDC
- Hydraulische druk: min. 120 bar, max. 220 bar
- Hydraulische flow: min. 20 ltr/min., max. 100 ltr/min.
- Balhoofdlengte: ± 281 cm
- L x B x H: ± 433x283x291 cm
- Gewicht: ± 1600 kg
- Kleuren: blauw / wit
- Opties:
 - transmitter met driepoot, handbaak
 - opbergboxen
 - verlichting
 - slopemeter (met visuele indicator)
 - New Holland tractor

KILVERBORD
RW280TK W.DU.E.M.PROP (double receivers)
HW-no.: 1108280



Technical specifications

- Accumulator pressostat system
- Working width: 283 cm with closed doors, 391 cm with open doors (only for fine leveling)
- Adjustable drawing eye cat. 3 Ø37.6 mm
- Blade height: ±110 cm
- Fitted with independent wheel suspension:
 - 1 hydraulic cylinder for height adjustment and blade leveling left
 - 1 hydraulic cylinder for height adjustment and blade leveling right
- 4 wheels BKT 19.0/45-R17/10PR AW-708, 49 cm wide each with one wheel scraper
- 2 hydraulic doors independently operated by a secondary controlbox
- Manually in height adjustable masts
- Secondary controlbox to operate the hydraulic doors and the height of the blade automatically or manually
- Complete with cabling and hydraulic connections
- Power supply: 12 or 24 VDC
- Hydraulic pressure: min. 120 bar, max. 220 bar
- Hydraulic flow: min. 20 ltr/min., max. 100 ltr/min.
- Length steering head: ± 281 cm
- L x W x H: ± 433x283x291 cm
- Weight: ± 1600 kg
- Colors: blue / white
- Options:
 - transmitter with stand, laser eye
 - storage boxes
 - lights
 - slope meter (with visual indicator)
 - New Holland tractor

