

**POMPUNIT**  
**Kubota V3600 / 2x Pratissoli KF40**  
**HW-nr.: 0893300**



## Technische specificaties

- KF40 dubbele plunjerpomp, drukregelaar, drukbeveiliging, manometer, Technodrive overbrenging 1:3  
capaciteit: 140 ltr/min., werkdruk: 80 kg/cm<sup>2</sup>- 80 bar
- Kubota V3600 4-cilinder watergekoelde dieselmotor 80 pk / 60 kW
- Inhoud brandstoftank: 153 ltr.
- Dieselbrandstofmeter en elektrische starter
- In buizen frame met trillingsdempers
- L x B x H: ± 178x78x147 cm
- Gewicht: ± 1335 kg
- Opties: gemonteerde zuigslang met zuigkorf  
gemonteerde retourslang  
gemonteerde hogedrukslang(en)  
toerenteller  
droogloop beveiliging

**PUMPUNIT**  
**Kubota V3600 / 2x Pratissoli KF40**  
**HW-no.: 0893300**



## Technical specifications

- KF40 double plunger pump, pressure regulator, pressure relieve valve, manometer, Technodrive transmission 1:3  
capacity: 140 ltr/min., pressure: 80 kg/cm<sup>2</sup> -80 bar
- Kubota V3600 4-cylinder water-cooled diesel engine 80 hp / 60 kW
- Capacity fuel tank: 153 ltr.
- Diesel fuel gauge and electrical start
- In steel frame with shock absorbers
- L x W x H: ± 178x78x146 cm
- Weight: ± 1335 kg
- Options: fitted suction hose with suction basket  
fitted return hose  
fitted high pressure hose(s)  
tachometer  
run dry protection