

**POMPUNIT
M60 3kW 400V
HW-nr.: 0930180**



Technische specificaties

- M60 membraanpomp, kleppen en zittingen van RVS, spuitstuk, C6 drukregelaar en manometer
- De onderdelen van het pompgedeelte welke in contact komen met de spuitvloeistof zijn gecoat
- Diameter aanzuigbocht: 30 mm, overloopbocht: 18 mm
- 2 kogelkranen met slangpilaar: 10 mm
- V-snaaroverbrenging met beschermkast
- Elektromotor: 1415 rpm, 400 V, 3 fase, 50 Hz, 4 pk / 3 kW, aan/uit schakelaar, thermische beveiliging en nulspanningspoel
- Geheel gemonteerd op frame
- Capaciteit: ± 35 ltr/min.
- Max. werkdruk: 40 kg/cm² (40 bar)
- L x B x H: ± 67x38x37 cm
- Gewicht: ± 60 kg
- Opties: Zuigfilter
Diverse slangen

**PUMPUNIT
M60 3kW 400V
HW-no.: 0930180**



Technical specifications

- M60 membrane pump, valves and seats of stainless steel, manifold, C6 regulating valve and manometer
- The parts of the pump side which come into contact with the spray liquid are coated
- Diameter of suction hose tail: 30 mm, overflow hose tail: 18 mm
- 2 ball valves with hose tail: 10 mm
- V-belt transmission with protection case
- Electric motor: 1415 rpm, 400 V, 3 phase, 50 Hz, 4 hp / 3 kW, on/off switch, thermal overload protection and zero voltage spool
- Mounted on frame
- Capacity: ±35 ltr/min.
- Max. pressure: 40 kg/cm² (40 bar)
- L x W x H: ± 67x38x37 cm
- Weight: ± 60 kgs
- Options: Suction filter
Various hoses