

SCHROB-/ZUIGMACHINE

Nilfisk-ALTO SCRUBTEC 661BL

HW-nr.: 0621661



SCRUBTEC 661

Gewoon een topserie

De SCRUBTEC 6-serie, de serie die de klant de keus biedt uit een aantal werkbreedtes. Naast de verwisselbare schrobdeks beschikt de machine over een uitzonderlijk laag geluidsniveau, instelbare borsteldruk en een bedieningspaneel dat ontworpen is om typische gebruikersfouten te voorkomen.

Geschikt voor eenvoudige, efficiënte reiniging in ziekenhuizen, winkels, fabrieken, garagebedrijven, magazijnen, restaurants, hotels en overal daar waar het belangrijk is dat de vloeren schoon blijven.

PRODUCT KENMERKEN

- Verwisselbare schrobdeks met twee afmetingen (53 cm en 61 cm) schijfborstel en 51 cm cilindrisch -55 Liter schoon.
- en vuilwatertank -Grote opening vergemakkelijkt het reinigen van de vuilwatertank -Instelbare borsteldruk garandeert de beste reinigingsresultaten onder alle omstandigheden.

	SCRUBTEC 661	SCRUBTEC 651	SCRUBTEC 653	
• Bron motorvermogen:	100	100	100	bat. ah
• Maximum snelheid:	5.6	5.6	-	km/u
• Voltage:	24	24	24	v
• Beschermingsklasse:	IPX4	IPX4	IPX4	elektr.
• Isolatieklasse:	III	III	III	
• Nominaal vermogen:	1230	1330	810	w
• Borstelmotor:	2x350	2x400	480	w
• Vermogen tractiemotor:	200	200	-	w
• Vermogen zuigmotor:	330	330	330	w
• Luchtstroom:	25.3	25.3	25.3	l/sec
• Vacuüm:	11	11	11	kpa
• Geluidniveau op 1,5 m ISO 3744:	65.8	65.8	65.8	db(a)
• Capaciteit:	2440	2040	2120	m ² /u
• Schrob breedte:	610	510	530	mm
• Draaicirkel:	70	70	70	cm
• Max. hellingspercentage:	16	16	-	%
• Waterhoeveelheid:	0.55-1.1	0.55-1.1	0.55-1.1	l/min
• Tankinhoud schoonwater-/vuilwater:	55/55	55/55	55/55	ltr
• Zuigmond breedte:	810	760	760	mm
• Borsteldruk:	27/47	28	25	kg
• Toerental borstel:	230	570	135	tpm
• Borsteldiameter:	2x305	2x510	530	mm
• Afmetingen L x B x H:	1310x650x1050	1250x570x1050	1320x540x1050	mm
• Gewicht:	110	112	88	kg
• Gewicht bij werking (alleen machine):	255	257	237	lb

SCRUBBER DRYER

Nilfisk-ALTO SCRUBTEC 661BL

HW-no.: 0621661



SCRUBTEC 661

Walk Behind 510/530/610 mm Battery & Mains Powered Scrubber Dryers

Named the SCRUBTEC 6 series, this range of machines offers a choice of scrubbing widths. Apart from the interchangeable brush deck, other features include an exceptionally low noise level, adjustable scrubbing pressure and dashboard that is designed to reduce typical operator errors.

Suitable for easy, efficient floor cleaning in hospitals, retail outlets, manufacturing plants, car dealers, garages, warehouses, restaurants, hotels, and other locations where it is important that floors are kept clean.

PRODUCT FACTS

- Interchangeable brush decks with 2 disc sizes (53 and 61 cm) or 51 cm cylindrical.
- 55 litres solution and recovery tanks.
- Large access to recovery tank speeds up cleaning time.
- Adjustable scrubbing pressure provides the best results under all conditions.

	SCRUBTEC 661	SCRUBTEC 651	SCRUBTEC 653	
• Motor power source:	Battery	Battery	Battery	
• Max. speed:	5.6	5.6	-	km./h
• Voltage:	24	24	24	v
• Protection class:	IPX4	IPX4	IPX4	electr.
• Insulation class:	III	III	III	
• Rated power:	1230	1330	810	w
• Brush motor:	2x350	2x400	480	w
• Traction motor power:	200	200	-	w
• Vacuum motor power:	330	330	330	w
• Airflow:	25.3	25.3	25.3	l/sec
• Vacuum:	11	11	11	kpa
• Sound pressure level at 1.5 m ISO 3744:	65.8	65.8	65.8	db(a)
• Productivity rate:	2440	2040	2120	m ² /h
• Scrubbing width:	610	510	530	mm
• Min. turn-around aisle width:	70	70	70	cm
• Max. climb rate:	16	16	-	%
• Water flow:	0.55-1.1	0.55-1.1	0.55-1.1	l/min
• Tank capacity solution/recovery:	55/55	55/55	55/55	ltr
• Squeegee width:	810	760	760	mm
• Brush pressure:	27/47	28	25	kg
• Brush speed:	230	570	135	rpm
• Brush size:	2x305	2x510	530	mm
• Dimensions L x W x H:	1310x650x1050	1250x570x1050	1320x540x1050	mm
• Weight:	110	112	88	kg
• Operating weight (machine only):	255	257	237	lb