

Veeg-zuigmachine Nilfisk-ALTO 6150 HW-nr.: 0626150



Stofvrije veeg -/zuigmachine. Krachtig. Extreem! De ALTO 6150 is opzit veeg -/zuigmachine met een hoge capaciteit, filterreiniging en variabele hoogtediging. Geschikt voor zwaarste, industriële toepassingen, b.v. grote parkeerterreinen, parkeergarages met meerdere verdiepingen etc.

Leverbaar in batterij -, LPG -, benzine - of dieselluitvoering.

De ALTO 6150 biedt u vele standaard kenmerken en een breed assortiment aan toebehoren en opties zodat de machine exact aan uw specifieke reinigingseisen aangepast kan worden.

Product kenmerken:

- Robuuste stalen constructie
- Filterreiniging voor continu stofvrij vegen
- 3-Fase filtersysteem
- Hoofd, achterkant en werktuiglichten
- Overzichtelijk bedieningspaneel voor eenvoudig gebruik
- Elektrische schudfilter
- Stuurbevestiging
- 283 liter vuilvergaarbak
- Groot filterelement en vuilreservoir
- Verstelbare stoel voor ergonomische werking

Technische specificaties:

- Werkbreedte met 1 rechter zijborstel: 1270 mm
- Werkbreedte met 2 zijborstels: 1520 mm
- Diameter zijborstel: 534 mm
- Vuilvergaarbak: 283 ltr.
- Filtermateriaal: papier
- Filteroppervlak: 7,2 m²
- Draaicirkel (links): 1360 mm
- L x B x H: 2210x1310x1350 mm
- Alternatief filter: polyester
- Filterreinigings systeem: elektrisch
- Aandrijfbron systeem: benzine 25 pk Kubota
Batterij 36 VDC
diesel 20 pk Kubota
- Maximum snelheid: batterij 6,5 km/u
LPG 8,5 km/u
diesel 13 km/u
- Gewicht met batterij: 1555 kg
LPG / Diesel 955 kg
- Max. hellingspercentage: 14 %
- Theoretische capaciteit: 7620 m²/uur

Sweeper
Nilfisk-ALTO 6150
HW-no.: 0626150



Dust free sweeping, Powerful Extreme! Ride-on sweeper with dust control and variable high dump. Used for even toughest industrial applications in or outdoor, warehouses, parking areas, multi-story car park etc.

Available in Battery, LP gas, Petrol or diesel versions.

The no tool broom adjustment is located in the driver compartment this together with the no tool filter, side broom and makes broom removal makes it very operator friendly

Product facts:

- Heavy steel construction
- Energy absorbing bumper
- Three stage filter system
- Head, tail and instrument lights
- Clear control panel for easy operation
- Electrical filter shaker
- Full time power steering
- 283 litres hopper
- Large filter and hopper
- Adjustable seat for ergonomic operation

Technical specifications:

- Sweeping path width side broom: 1270 mm
- Working width 2 side brushes: 1520 mm
- Side broom diameter: 534 mm
- Hopper volume: 283 ltr.
- Filter material: paper
- Filter surface: 7,2 m²
- Turn-around aisle width: 1360 mm
- L x B x H: 2210x1310x1350 mm
- Alternative filter: Polyester
- Filter cleaning system: electrical
- Drive well system:
 - engine 25 hp Kubota
 - battery 36 VDC
 - diesel 20 hp Kubota
- Maximum fastness:
 - Battery 6,5 km/h
 - LPG 8,5 km/h
 - diesel 13 km/h
- Weight with battery:
 - 1555 kgs
 - LPG/ diesel 955 kgs
- Max. climbing rate: 14 %
- Theoretical surface performance: 7620 m²/h