

**SPIITWAGEN 4-WIELIG 600L KUIP**  
**pomp P63 / V-snaren**  
**HW-nr.: 0924179**



### Technische specificaties

- Smitwagen vierwielig 400x8 6pr met trekboombesturing, ophangbeugel, snoergeleider
- Parkeerrem op achterwiel
- Polyester transparante 600 ltr. kuip met aan zijden maatverdeling, antikolk inlaat, schroefdeksel met 2 ontluuchtingskleppen, fustenreiniger, aftapbak met kogelkraan en Geka-koppeling voor vullen of aftappen
- P63 plunjerpomp, C6 drukregelaar, manometer, 2x kogelkraan, V-snaar overbrenging, elektromotor 400 V 4 kW / 5,5 pk, capaciteit: 42 ltr/min., werkdruk: 50 kg/cm<sup>2</sup> - 50 bar
- Zuigslang met filter boven vloeistofniveau, overloopslang en roerslang met 2x roerinjecteur 1/2"
- L x B x H:           ± 183x115x142 cm
- Gewicht:             ± 210 kg
- Opties:               (draaibaar) handhaspel  
                          (draaibaar) verend haspel  
                          3/8" haspelslang  
                          elektrische slanghaspel: WCR

**PUMPCAR FOURWHEEL 600L BARREL**  
**pump p63 / V-belt**  
**HW-no.: 0924179**



## Technical specifications

- Pumpcar fourwheel 400x8 6pr with towing lever control, drop hanger, flex-cord guide
- Parking brake on rear wheel
- Polyester transparent 600 ltr. barrel with both sides capacity markings, anti swirl intake, threaded lid with 2 breather valves, packing cleaner, drainage area with ball valve and Geka-joint for fill or drain
- P63 plunger pump, C6 pressure regulator, manometer, 2x ball valves, V-belt transmission, electric motor 400 V 4 kW / 5,5 hp, capacity: 42 ltr/min., pressure: 50 kg/cm<sup>2</sup> - 50 bar
- Suction hose with filter above liquid level and overflow hose, stirring hose with 2x stir ejector 1/2"
- L x W x H:           ± 183x115x142 cm
- Weight:               ± 210 kgs
- Options:             (turnable) hand hose roller  
                           (turnable) hose roller powered by spring  
                           3/8" hose for roller  
                           electric hose roller: WCR