

SPUITWAGEN 3-WIELIG 200L TANK
pomp T531
HW-nr.: 0925050



Technische specificaties

- Suiptwagen 3 wielig 400x8-4pr met trekboombesturing
- Polyester transparante 200 ltr. tank met maatverdeling, antikolk inlaat, schroefdeksel met 2 ontluichtingskleppen en aftapbak met kogelkraan en Geka-koppeling voor vullen of aftappen
- T531 plunjerpomp met 2 zuigers van ceramiek, kleppen en zittingen van R.V.S., spuitstuk, drukregelaar C6 en manometer, elektromotor 230 V 1,5 kW / 2 pk, capaciteit: 11 ltr/min., werkdruk: 50 kg/cm² - 50 bar
- Zuigslang met filter boven vloeistofniveau, overloopslang en roerslang met 1x roerinjecteur 1/2"
- L x B x H: ± 144x86x114 cm
- Gewicht: ± 160 kg
- Opties: hand- of verend haspel (draaibaar met blokkering in 3 standen)
haspelslang max. 100 mtr. 3/8"
4 wielig 400x8-4pr

PUMPCAR THREE WHEEL 200L TANK
pump T531
HW-no.: 0925050



Technical specifications

- Pumpcar three wheel 400x8-4pr with towing lever control
- Polyester transparent 200 ltr. tank with capacity markings, anti swirl intake, threaded lid with 2 breather valves and drainage area with ball valve and Geka-joint for fill or drain
- T531 plunger pump with 2 pistons of ceramic, valves and seats of stainless steel, manifold, regulating valve C6 and manometer, electric motor 230 V 1,5 kW / 2 hp, capacity: 11 ltr/min., pressure: 50 kg/cm² - 50 bar
- Suction hose with filter above liquid level and overflow hose, stirring hose with 1x stir ejector 1/2"
- L x W x H: ± 144x86x114 cm
- Weight: ± 160 kgs
- Options: manual or spring powered hose roller (turnable with locking in 3 positions)
hose for roller max. 100 mtr. 3/8"
four wheel 400x8-4pr