



SPUITWAGEN 4-WIELIG 600L TANK pomp T531 / Weri Compact Roller HW-nr.: 0925500



Technische specificaties

- Smitwagen vierwielig 400x8 6pr met trekboombesturing, ophangbeugel, snoergeleider
- Parkeerrem op achterwiel
- Polyester transparante 600 ltr. tank met maatverdeling, antikolk inlaat, schroefdeksel met 2 ontluichtingskleppen en aftapbak met kogelkraan en Geka-koppeling voor vullen of aftappen
- T531 plunjerpomp met 2 zuigers van ceramiek, kleppen en zittingen van R.V.S., spuitstuk, drukregelaar C6 en manometer, elektromotor 400 V 1,5 kW / 2 pk, capaciteit: 11 ltr/min., werkdruk: 50 kg/cm² - 50 bar
- Zuigslang met filter boven vloeistofniveau, overloopslang en roerslang met 1x roerinjecteur 1/2"
- Weri Compact Roller vast gemonteerd op spuitwagen, 3/4" doorlaat, slanggeleider voor , 3/4" slang, manuele variator voor traploos regelbare oprolsnelheid (0-55 mtr/min.), Tele Radio handzender om de Weri Compact Roller op afstand aan/uit te zetten en af te remmen, maximale bereik: ±100 mtr. (afhankelijk van omstandigheden), elektrische vrijloopkoppeling, instelbare aflooprem en elektromotor 400 V
- L x B x H: ± 322x102x142 cm
- Gewicht: ± 310 kg
- Opties: handhaspel
verend haspel
draibare WCR



PUMPCAR FOURWHEEL 600L TANK
pump T531 / Weri Compact Roller
HW-no.: 0925500



Technical specifications

- Pumpcar fourwheel 400x8 6pr with towing lever control, drop hanger, flex-cord guide
- Parking brake on rear wheel
- Polyester transparent 600 ltr. tank with capacity markings, anti swirl intake, threaded lid with 2 breather valves and drainage area with ball valve and Geka-joint for fill or drain
- T531 plunger pump with 2 pistons of ceramic, valves and seats of stainless steel, manifold, regulating valve C6 and manometer, electric motor 400 V 1,5 kW / 2 hp, capacity: 11 ltr/min., pressure: 50 kg/cm² - 50 bar
- Suction hose with filter above liquid level and overflow hose, stirring hose with 1x stir ejector 1/2"
- Weri Compact Roller fixed mounted behind pump car, 3/4" swivel, hose guide for 3/4" hose, automatic reduction, continuously variable roll up speed (0-55 mtr/min.) manually controlled, radiographic control for on/off and brake by Tele Radio transmitter, max. reach: ±100 mtr. (depending on circumstances), electric freewheel clutch, adjustable roll off brake and electric motor 400 V
- L x W x H: ± 322x102x142 cm
- Weight: ± 310 kgs
- Options: hose roller powered by hand
hose roller powered by spring
turnable mounted WCR