



**WETERINGS**<sup>®</sup>  
MECHANISATIE

## Doekoproller mobiel speciaal HW-nr.: 2460025



**WETERINGS MECHANISATIE** | INCOMPARABLE IN HORTICULTURAL TECHNIQUE

OUDE HOOSLAG 4, 2691 NH 'S-GRAVENZANDE, HOLLAND

C.O.C. HAAGLANDEN NO.: 27219130

**T:** +31 (0)174 41 64 81

VAT NO.: NL004850786B01

**F:** +31 (0)174 41 40 28

IBAN NL79 INGB 0659 41 17 76, SWIFTCODE: INGBNL2A

**I:** WWW.WETERINGS.NL

All our quotations, all orders placed with us and all contracts concluded with us are subject to the METAALUNIECONDITIONS, filed with the registrar of the District Court of Rotterdam, as stipulated in the latest text lodged with the said court. The conditions of delivery and payment will be sent to you upon request.

220611-A-FOL

## Technische specificaties

1. PVG32 ventiel met beveiliging tegen retourbelasting en 4 functies:  
2x doekoproller, 1x sturen en 1x band
2. Spijlenband met canvasdoek
3. Draaibaar trekoog cat. 2 Ø25,7 mm -/- cat. 3 Ø37,6 mm
4. Trekboom hydraulisch draaibaar met hoogte verstelling en steunwiel
5. Wielas in hoogte verstelbaar met 2 stuks 24X13.00-12/4PR 5-gaats banden
6. Compleet met bekabeling, noodstopknoppen en hydrauliek slangen met ½" snelsluiters
7. Voedingsspanning: 12 of 24 VDC
8. Hydraulische druk: min. 120 bar, max. 220 bar
9. Hydraulische flow: min. 40 ltr/min., max. 100 ltr/min.
10. Capaciteit: max. afvoeren: ± 3000 - 7500 m<sup>2</sup>/uur (afh. van omstandigheden)  
max. lengte gronddoek: ± 120 m
11. L x B x H: ± 495x175x190 cm
12. Gewicht: ± 910 kg
13. Kleuren: blauw / wit
14. Opties: Onboard hydrauliekunit met aandrijving via PTO Tractor  
Onboard hydrauliekunit met elektromotor 10 pk-7,5 kW, 400 V, 3 fase  
Verlichting  
New Holland tractor



## Technical specifications

1. PVG32 valve with safety device against return pressure and 4 functions:  
2x roll up implement, 1x steering and 1x belt
2. Belt with link bars and canvas
3. Adjustable drawing eye cat. 2 Ø25,7 mm -/- cat. 3 Ø37,6 mm
4. Drawing beam with hydraulic steering, height adjustment and support wheel
5. Wheel axle in height adjustable with 2 pieces of 24X13.00-12/4PR 5-holes tires
6. Complete with cabling, emergency stops and hydraulic hoses with ½" quick couplings
7. Power supply: 12 or 24 VDC
8. Hydraulic pressure: min. 120 bar, max. 220 bar
9. Hydraulic flow: min. 40 ltr/min., max. 100 ltr/min.
10. Capacity: max. processing: ± 3000 - 7500 m<sup>2</sup>/h (depending on circumstances)  
max. length transport mat: ± 120 m
11. L x W x H: ± 495x175x190 cm
12. Weight: ± 910 kg
13. Colors: blue / white
14. Options: Onboard hydraulic unit with power supply of PTO Tractor  
Onboard hydraulic unit with electric motor 10 hp–7,5 kW, 400 V, 3 phase  
Lighting  
New Holland tractor





## Doekoproller mobiel speciaal HW-nr.: 2460025

